

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 1 (original) An improved filter assembly for a circuit breaker comprising:
a generally rectilinear filter housing having at least two filter mounting zones for receiving at least two filter assemblies, so as to define, in the aggregate, a filter assembly; and
at least two filter assemblies configured for interfitting with said filter mounting zones of said filter housing, each said filter assembly comprising a generally rectilinear filter body having a given peripheral configuration and a filter gasket configured for interfitting about a periphery of said filter body for sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assembly both upon assembly and in operation.

Claim 2 (original) The assembly of claim 1 wherein said filter gaskets are comprised of a silicone material.

Claim 3 (original) The assembly of claim 1 wherein each of said filter bodies has a peripheral recessed portion for positioning, mounting and bearing against a complementary edge portion of said filter gasket.

Claim 4 (original) The filter assembly of claim 3 and further including:
a small hole diffuser having a peripheral configuration similar to the peripheral configuration of said filter bodies, in the aggregate, when assembled with said filter housing and configured for interfitting within said filter housing, superimposed over said filter assemblies;
a spacer interposed between said filters and said small hole diffuser; and
a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, said coarse hole diffuser including means for engaging and interfitting with said filter housing in close overlying engagement with said small hole diffuser.

Claim 5 (original) The assembly of claim 4 wherein said coarse hole diffuser further includes means for cooperatively interfitting with a plurality of arc plates of an arc diffuser plate assembly, including means for locating and engaging said coarse hole diffuser relative to said arc plate assembly and means for engaging and maintaining a plurality of plates of said arc plate assembly in parallel and spaced apart condition.

RA
Claim 6 (original) The assembly of claim 1 wherein said filter housing comprises a frame-like, one-piece molded member having a recessed area for receiving each of said filter elements and an associated gasket therewithin, including separate areas for cooperatively interfitting with and bearing against edges of said gaskets opposite edges thereof bearing against said filter elements, and a projecting frame-like peripheral portion extending outwardly for surrounding engagement with said filter elements, said spacer and said small hole diffuser.

Claim 7 (original) The assembly of claim 6 wherein said coarse hole diffuser further includes a peripheral flange at least along portions of a periphery thereof for engaging with and seating relative to a complementary peripheral flange portion of said filter housing.

Claim 8 (original) The assembly of claim 5 in combination with a circuit breaker housing and arc stack, and further including complementary projections and slots formed respectively on said arc stack, said coarse hole diffuser and said breaker housing for positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case.

Claim 9 (currently amended) A molded coarse hole diffuser for a filter assembly for use with a circuit breaker, said molded coarse hole diffuser comprising a combined coarse hole diffuser and spacer integrally molded as a single, one-piece unit, said coarse hole diffuser including means for engaging and interfitting with a filter housing in close overlying engagement with a small hole diffuser.

Claim 10 (original) The diffuser of claim 9 wherein said coarse hole diffuser further includes means for cooperatively interfitting with a plurality of arc plates of an arc diffuser plate assembly, including means for locating and engaging said coarse hole diffuser relative to said arc plate assembly and means for engaging and maintaining a plurality of plates of said arc plate assembly in parallel and spaced apart condition.

RA
Claim 11 (original) The diffuser of claim 9 wherein said coarse hole diffuser further includes a peripheral flange at least along portions of the periphery thereof for engaging with and seating relative to a complementary peripheral flange portion of said filter housing.

Claim 12 (original) The diffuser of claim 11 in combination with a circuit breaker housing and arc stack, and further including complementary projections and slots formed respectively on said arc stack, said coarse hole diffuser and said breaker housing for positioning and maintaining said arc stack and a filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case.

Claim 13 (original) A circuit breaker assembly comprising:

a filter assembly comprising:

a generally rectilinear filter housing having at least two filter mounting zones for receiving at

least two filter assemblies, so as to define, in the aggregate, a filter assembly; and

at least two filter assemblies configured for interfitting with said filter mounting zones of said

filter housing, each said filter assembly comprising a generally rectilinear filter body

having a given peripheral configuration and a filter gasket configured for interfitting

about a periphery of said filter body for sealingly engaging said filter body relative to said

filter housing in response to forces encountered by said filter assembly both upon

assembly and in operation;

a small hole diffuser having a peripheral configuration similar to the peripheral configuration of said filter bodies, in the aggregate, when assembled with said filter housing and configured for interfitting within said filter housing, superimposed over said filter assemblies;

a spacer interposed between said filters and said small hole diffuser; and

a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, said coarse hole diffuser including means for engaging and interfitting with said filter housing in close overlying engagement with said small hole diffuser.

Claim 14 (original) The assembly of claim 13 in combination with a circuit breaker housing and an arc stack, and further including complementary projections and slots formed respectively on said arc stack, said coarse hole diffuser and said breaker housing for positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case.

Claim 15 (currently amended) A method of filtering high energy arcing in a circuit breaker comprising:

mounting at least two filter assemblies with a generally rectilinear filter housing having at least two filter mounting zones so as to define, in the aggregate, a filter assembly; and

sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assembly both ~~during~~ ^{at} ~~during~~ assembly and in operation.

at use

Claim 16 (original) The method of claim 15 wherein said sealingly engaging includes interfitting a filter gasket comprised of a silicone material with each filter element.

Claim 17 (original) The method of claim 16 wherein said sealing includes positioning peripheral recessed portion of each filter body for bearing against a complementary edge portion of one of said filter gaskets.

Claim 18 (original) The method of claim 15 and further including:

assembling a small hole diffuser having a peripheral configuration similar to the peripheral configuration of said filter bodies in the aggregate, when assembled, with said filter housing, and interfitting within said filter housing superimposed over said filter assemblies;

interposing a spacer between said filters and said small hole diffuser; and

engaging a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, with said filter housing in close overlying engagement with said small hole diffuser.

Claim 19 (original) The method of claim 18 further including cooperatively interfitting said coarse hole diffuser with a plurality of arc plates of an arc diffuser plate assembly, including locating and engaging said coarse hole diffuser relative to said arc plate assembly so as to engage and maintain a plurality of plates of said arc plate assembly in parallel and spaced apart condition.

Claim 20 (original) The method of claim 15 wherein said mounting comprises receiving filter elements and gaskets within a recessed area of a frame-like, one-piece molded member comprising said filter housing, including cooperatively interfitting with and bearing against edges of said gaskets opposite edges thereof bearing against said filter elements, and said filter housing surroundingly engaging said filter elements, said spacer and said small hole diffuser.

Claim 21 (original) The method of claim 20 further including engaging and seating a peripheral flange of said coarse hole diffuser relative to a complementary peripheral flange portion of said filter housing.

Claim 22 (original) The method of claim 19 and further including positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case, utilizing complementary projections and slots formed respectively on said arc stack, said coarse hole diffuser and said breaker housing.

RA
Claim 23 (original) A method of suppressing arcing in a circuit breaker comprising:
a method filtering a high energy arc comprising:
mounting at least two filter assemblies with a generally rectilinear filter housing having at least two filter mounting zones so as to define, in the aggregate, a filter assembly;
sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assembly both during assembly and in operation;
assembling a small hole diffuser having a peripheral configuration similar to the peripheral configuration of said filter bodies in the aggregate, when assembled, with said filter housing and interfitting within said filter housing superimposed over said filter assemblies;
interposing a spacer between said filters and said small hole diffuser; and
engaging a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, with said filter housing in close overlying engagement with said small hole diffuser; and
a method for diffusing said arc, comprising:
positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case, utilizing complementary projections and slots formed respectively on said arc stack, said coarse hole diffuser and said breaker housing.

Claim 24 (original) A filter assembly comprising:

means for mounting at least two filter assemblies with a generally rectilinear filter housing having at least two filter mounting zones so as to define, in the aggregate, a filter assembly; and

means for sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assembly both during assembly and in operation.

Claim 25 (original) The assembly of claim 24 wherein said means for sealingly engaging includes means for interfitting a filter gasket comprised of a silicone material with each filter element.

Claim 26 (currently amended) The assembly of claim 25 wherein said ~~means~~ means for sealing includes means for positioning peripheral recessed portion of each filter body for bearing against a complementary edge portion of one of said filter gaskets.

Claim 27 (original) The assembly of claim 24 and further including:

means for assembling a small hole diffuser having a peripheral configuration similar to the peripheral configuration of said filter bodies in the aggregate, when assembled with said filter housing, and for interfitting within said filter housing superimposed over said filter assemblies;

means for interposing a spacer between said filters and said small hole diffuser; and

means for engaging a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, with said filter housing in close overlying engagement with said small hole diffuser.

Claim 28 (original) The assembly of claim 27 further including means for cooperatively interfitting said coarse hole diffuser with a plurality of arc plates of an arc diffuser plate assembly, including means for locating and engaging said coarse hole diffuser relative to said arc plate assembly so as to engage and maintain a plurality of plates of said arc plate assembly in parallel and spaced apart condition.

Claim 29 (original) The assembly of claim 24 wherein said means for mounting comprises means for receiving filter elements and gaskets within a recessed area of a frame-like, one-piece molded member comprising said filter housing, including means for cooperatively interfitting with and bearing against edges of said gaskets opposite edges thereof bearing against said filter elements, and said filter housing, including means for surroundingly engaging said filter elements, said spacer and said small hole diffuser.

Claim 30 (original) The assembly of claim 29 further including means for engaging and seating a peripheral flange of said coarse hole diffuser relative to a complementary peripheral flange portion of said filter housing.

Claim 31 (original) The assembly of claim 28 and further including means for positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including means for maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, for equalizing compression loading of said gaskets and for providing final positioning of the arc stack and filter assembly into the breaker case.

Claim 32 (original) A circuit breaker assembly comprising:
means for filtering a high energy arc comprising:
means for mounting at least two filter assemblies with a generally rectilinear filter housing
having at least two filter mounting zones so as to define, in the aggregate, a filter
assembly;
means for sealingly engaging said filter body relative to said filter housing in response to forces
encountered by said filter assembly both during assembly and in operation;
means for assembling a small hole diffuser having a peripheral configuration similar to the
peripheral configuration of said filter bodies in the aggregate, when assembled, with said
filter housing and interfitting within said filter housing, superimposed over said filter
assemblies;
means for interposing a spacer between said filters and said small hole diffuser; and

means for engaging a molded coarse hole diffuser, defining a combined diffuser and spacer integrally molded as a single, one-piece unit, with said filter housing in close overlying engagement with said small hole diffuser; and

means for diffusing said arc, comprising:

means for positioning and maintaining said arc stack and said filter assembly in assembled relation within said breaker housing, including maintaining compression on said gaskets and maintaining constant assembly force upon said assembly, equalizing compression loading of said gaskets and providing final positioning of the arc stack and filter assembly into the breaker case.

Claim 33 (new) A method for assembling a circuit breaker assembly, comprising:

providing a generally rectilinear filter housing and at least two filter assemblies, said filter housing having at least two filter mounting zones, each of said filter assemblies including a generally rectilinear filter body having a peripheral configuration;

interfitting a filter gasket about a periphery of said filter body for sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assemblies both upon assembly and in operation; and

interfitting said filter assemblies in said filter mounting zones, each of said filter mounting zones receiving one of said filter assemblies.

Claim 34 (new) A circuit breaker assembly, comprising:

a generally rectilinear filter housing having at least two filter mounting zones; and

at least two filter assemblies, each of said filter assemblies being configured for interfitting a respective one of said filter mounting zones, each of said filter assemblies including

a generally rectilinear filter body having a given peripheral configuration and

a filter gasket configured for interfitting about a periphery of said filter body for sealingly engaging said filter body relative to said filter housing in response to forces encountered by said filter assembly both upon assembly and in operation.